



# Rundrohre

Legierung Al Mg Si 0,5 F 22 gepresst, warm ausgehärtet, in Herstellungslängen nach **EN 573 -3, 755 -1/ -2/ -7/ -8/ -9, DIN 1748 -3/ -4, 9107**

Durchmesser mm	Stärke mm	Gewicht kg/m	Al Mg Si 0,5 F 22 (EM AW-6060 T66)
6 x	1,0	0,042 *	●
8 x	1,0	0,059 *	●
10 x	1,0	0,076 *	●
10 x	1,5	0,108 *	●
10 x	2,0	0,136 *	●
12 x	1,0	0,093 *	●
12 x	1,5	0,134 *	●
12 x	2,0	0,170 *	●
13 x	3,0	0,254 *	●
14 x	2,0	0,204 *	●
15 x	1,0	0,119 *	●
15 x	1,0	0,119 *	●
15 x	1,5	0,172 *	●
15 x	2,0	0,221 *	●
16 x	1,0	0,127 *	●
16 x	1,5	0,184 *	●
16 x	2,0	0,238 *	●
16 x	2,5	0,286 *	●
18 x	1,0	0,144 *	●
18 x	1,5	0,210 *	●
18 x	2,0	0,271 *	●
18 x	3,0	0,382 *	●
19 x	1,0	0,153 *	●
20 x	1,0	0,161 *	●
20 x	1,5	0,235 *	●
20 x	2,0	0,305	●
20 x	2,0	0,305 *	●
20 x	2,5	0,371	●
20 x	3,0	0,433	●
20 x	4,0	0,543 *	●
20 x	5,0	0,636 *	●
22 x	1,0	0,178 *	●
22 x	1,5	0,261 *	●
22 x	3,0	0,483 *	●
24 x	1,5	0,286 *	●
25 x	1,0	0,204 *	●
25 x	1,5	0,299 *	●
25 x	2,0	0,390	●
25 x	2,5	0,477	●
25 x	3,0	0,560	●

● auf Lager (1-2 bzw. 2-3 Arbeitstage) ● lieferbar (2-3 bzw. 3-4 Arbeitstage) \* SA= Sonderabmessungen

weitere Abmessungen auf Anfrage



# Rundrohre

Legierung Al Mg Si 0,5 F 22 gepresst, warm ausgehärtet, in Herstellungslängen nach **EN 573 -3, 755 -1/ -2/ -7/ -8/ -9, DIN 1748 -3/ -4, 9107**

Druchmesser mm	Stärke mm	Gewicht kg/m	Al Mg Si 0,5 F 22 (EM AW-6060 T66)
25 x	5,0	0,848	●
28 x	1,5	0,337	●
28 x	2,0	0,441	●
28 x	3,0	0,636 *	●
28 x	4,0	0,814 *	●
30 x	1,5	0,363 *	●
30 x	2,0	0,475	●
30 x	2,5	0,583	●
30 x	3,0	0,687	●
30 x	4,0	0,882	●
30 x	5,0	1,060	●
32 x	1,5	0,388 *	●
32 x	2,0	0,509	●
32 x	3,0	0,738	●
33 x	2,0	0,526 *	●
35 x	1,5	0,426 *	●
35 x	2,0	0,560	●
35 x	2,5	0,689	●
35 x	3,0	0,814	●
35 x	4,0	1,052	●
35 x	5,0	1,272	●
38 x	1,5	0,464 *	●
38 x	3,0	0,891	●
40 x	1,5	0,490 *	●
40 x	2,0	0,645	●
40 x	2,0	0,645	●
40 x	2,5	0,795	●
40 x	3,0	0,942	●
40 x	4,0	1,221	●
40 x	5,0	1,484	●
40 x	10,0	2,545 *	●
42 x	1,5	0,515 *	●
42 x	2,0	0,679	●
42 x	2,5	0,838	●
42 x	3,0	0,992	●
42 x	3,5	1,143 *	●
42 x	4,0	1,289 *	●
45 x	1,5	0,553 *	●
45 x	2,0	0,729	●
45 x	2,5	0,901	●



# Rundrohre

Legierung Al Mg Si 0,5 F 22 gepresst, warm ausgehärtet, in Herstellungslängen nach **EN 573 -3, 755 -1/ -2/ -7/ -8/ -9, DIN 1748 -3/ -4, 9107**

Durchmesser mm	Stärke mm	Gewicht kg/m	Al Mg Si 0,5 F 22 (EM AW-6060 T66)
45 x	3,0	1,069	●
45 x	5,0	1,696	●
46 x	3,0	1,094 *	●
48 x	2,5	0,965 *	●
48 x	3,0	1,145	●
48 x	4,0	1,493 *	●
50 x	1,5	0,617 *	●
50 x	1,5	0,617	●
50 x	2,0	0,714	●
50 x	2,5	1,007	●
50 x	3,0	1,196	●
50 x	4,0	1,561	●
50 x	5,0	1,909	●
50 x	10,0	3,393 *	●
54 x	2,0	0,882 *	●
55 x	2,5	1,113	●
55 x	5,0	2,121 *	●
56 x	3,0	1,349 *	●
58 x	3,0	1,400 *	●
60 x	1,5	0,744 *	●
60 x	2,0	0,983	●
60 x	2,5	1,219	●
60 x	3,0	1,450	●
60 x	4,0	1,900	●
60 x	5,0	2,333	●
60 x	6,0	2,748	●
60 x	10,0	4,241 *	●
65 x	2,0	1,069 *	●
65 x	2,5	1,325	●
65 x	2,5	1,325	●
65 x	5,0	2,545	●
66 x	3,0	1,603 *	●
70 x	2,0	1,154	●
70 x	3,0	1,705	●
70 x	4,0	2,239	●
70 x	5,0	2,757	●
70 x	10,0	5,089 *	●
75 x	2,5	1,537 *	●
75 x	5,0	2,969	●
76 x	2,5	1,559	●

● auf Lager (1-2 bzw. 2-3 Arbeitstage) ● lieferbar (2-3 bzw. 3-4 Arbeitstage) \* SA= Sonderabmessungen

weitere Abmessungen auf Anfrage



# Rundrohre

Legierung Al Mg Si 0,5 F 22 gepresst, warm ausgehärtet, in Herstellungslängen nach **EN 573 -3, 755 -1/ -2/ -7/ -8/ -9, DIN 1748 -3/ -4, 9107**

Durchmesser mm	Stärke mm	Gewicht kg/m	Al Mg Si 0,5 F 22 (EM AW-6060 T66)
76 x	3,0	1,858	●
80 x	2,0	1,323	●
80 x	2,5	1,643	●
80 x	3,0	1,959	●
80 x	4,0	2,579 *	●
80 x	5,0	3,181	●
80 x	10,0	5,938	●
80,4 x	4,5	2,897	●
84 x	2,0	1,391 *	●
85 x	5,0	3,393 *	●
86 x	3,0	2,112	●
90 x	2,0	1,493 *	●
90 x	3,0	2,214	●
90 x	5,0	3,605	●
90 x	10,0	6,786 *	●
100 x	2,0	1,663 *	●
100 x	2,5	2,068	●
100 x	3,0	2,468	●
100 x	4,0	3,257	●
100 x	5,0	4,029	●
100 x	6,0	4,784 *	●
100 x	10,0	7,634	●
105 x	2,5	2,174 *	●
106 x	3,0	2,621	●
106 x	3,0	2,621	●
108 x	3,0	2,672 *	●
108 x	4,0	3,529	●
110 x	3,0	2,723 *	●
110 x	5,0	4,453	●
110 x	10,0	8,482 *	●
114,3 x	3,0	3,029 *	●
115 x	5,0	4,665	●
120 x	3,0	2,977 *	●
120 x	4,0	3,936 *	●
120 x	5,0	4,877	●
120 x	8,0	7,600 *	●
125 x	4,0	4,105 *	●
125 x	10,0	9,755 *	●
130 x	3,0	3,232 *	●
130 x	5,0	5,301	●

● auf Lager (1-2 bzw. 2-3 Arbeitstage) ● lieferbar (2-3 bzw. 3-4 Arbeitstage) \* SA= Sonderabmessungen

weitere Abmessungen auf Anfrage



# Rundrohre

Legierung Al Mg Si 0,5 F 22 gepresst, warm ausgehärtet, in Herstellungslängen nach **EN 573 -3, 755 -1/-2/-7/-8/-9, DIN 1748 -3/-4, 9107**

Durchmesser mm	Stärke mm	Gewicht kg/m	Al Mg Si 0,5 F 22 (EM AW-6060 T66)
130 x	5,0	5,301	●
130 x	15,0	14,632 *	●
133 x	3,0	3,308 *	●
133 x	4,0	4,409 *	●
140 x	4,0	4,614 *	●
140 x	5,0	5,726	●
140 x	5,0		●
150 x	3,0	3,741	●
150 x	5,0	6,150	●
156 x	3,0	3,893 *	●
159 x	4,0	5,259 *	●
160 x	4,0	5,293 *	●
160 x	5,0	6,574 *	●
168 x	3,5	4,884 *	●
170 x	5,0	6,998 *	●
180 x	5,0	7,422 *	●
140 x	4,0	4,614 *	●
140 x	5,0	5,726	●
140 x	5,0		●
150 x	3,0	3,741	●
150 x	5,0	6,150	●
156 x	3,0	3,893 *	●
159 x	4,0	5,259 *	●
160 x	4,0	5,293 *	●
160 x	5,0	6,574 *	●
168 x	3,5	4,884 *	●
170 x	5,0	6,998 *	●
180 x	5,0	7,422 *	●
200 x	5,0	8,270 *	●
208 x	4,0	7,492 *	●
210 x	5,0	8,694 *	●
219 x	4,0	7,851 *	●
250 x	5,0	11,486 *	●
258 x	4,0	9,903 *	●
273 x	4,5	11,398 *	●
300 x	4,0	11,924 *	●
323,9 x	5,5	15,494 *	●

● auf Lager (1-2 bzw. 2-3 Arbeitstage) ● lieferbar (2-3 bzw. 3-4 Arbeitstage) \* SA= Sonderabmessungen

weitere Abmessungen auf Anfrage