


Vierkant- und Rechteckrohre

Legierung Al Mg Si 0,5 F 22 gepresst, warm ausgehärtet, in Herstellungslängen nach **EN 573 -3, 755 -1/ -2/ -9, DIN 1748 -4**

Höhe mm	Breite mm	Stärke mm	Gewicht kg/m	Al Mg Si 0,5 F 22 (EM AW-6060 T66)
50 x	20 x	4,0	1,339	●
50 x	25 x	2,0	0,767 *	●
50 x	25 x	2,0	0,775	●
50 x	25 x	2,5	0,945	●
50 x	25 x	3,0	1,118	●
50 x	30 x	2,0	0,821	●
50 x	30 x	2,5	1,013	●
50 x	30 x	3,0	1,199	●
50 x	34 x	3,0	1,264	●
50 x	40 x	2,0	0,929	●
50 x	40 x	2,5	1,148	●
50 x	40 x	3,0	1,361	●
50 x	40 x	4,0	1,771 *	●
50 x	45 x	2,0	0,983	●
50 x	50 x	2,0	0,713	●
50 x	50 x	2,5	1,283	●
50 x	50 x	3,0	1,523	●
50 x	50 x	4,0	1,987 *	●
50 x	50 x	5,0	2,430 *	●
55 x	50 x	3,0	1,604 *	●
55 x	55 x	2,0	1,145 *	●
56 x	31 x	2,5	1,107	●
60 x	20 x	2,0	0,821 *	●
60 x	20 x	3,0	1,199	●
60 x	20 x	4,0	1,555	●
60 x	25 x	2,0	0,875	●
60 x	25 x	3,0	1,280	●
60 x	30 x	2,0	0,929 *	●
60 x	30 x	2,0	0,929	●
60 x	30 x	3,0	1,361	●
60 x	34 x	3,0	1,426	●
60 x	40 x	2,0	1,037	●
60 x	40 x	2,5	1,283 *	●
60 x	40 x	2,5	1,283	●
60 x	40 x	3,0	1,523 *	●
60 x	40 x	3,0	1,523	●
60 x	40 x	4,0	1,987	●
60 x	50 x	3,0	1,685	●
60 x	50 x	4,0	2,203	●
60 x	60 x	2,0	1,253	●

● auf Lager (1-2 bzw. 2-3 Arbeitstage) ● lieferbar (2-3 bzw. 3-4 Arbeitstage) * SA= Sonderabmessungen

weitere Abmessungen auf Anfrage




Vierkant- und Rechteckrohre

Legierung Al Mg Si 0,5 F 22 gepresst, warm ausgehärtet, in Herstellungslängen nach **EN 573 -3, 755 -1/ -2/ -9, DIN 1748 -4**

Höhe mm	Breite mm	Stärke mm	Gewicht kg/m	Al Mg Si 0,5 F 22 (EM AW-6060 T66)
60 x	60 x	2,5	1,553	●
60 x	60 x	3,0	1,847 *	●
60 x	60 x	4,0	2,419	●
60 x	60 x	5,0	2,970	●
65 x	20 x	2,0	0,875 *	●
65 x	65 x	2,5	1,688 *	●
70 x	20 x	2,0	0,929 *	●
70 x	25 x	2,5	1,215	●
70 x	30 x	2,0	1,037	●
70 x	30 x	3,0	1,523 *	●
70 x	40 x	3,0	1,685 *	●
70 x	50 x	4,0	2,420 *	●
70 x	70 x	2,0	1,469 *	●
70 x	70 x	4,0	2,851	●
75 x	50 x	3,0	1,928	●
80 x	20 x	2,0	1,037	●
80 x	20 x	2,5	1,283	●
80 x	25 x	2,0	1,091	●
80 x	30 x	2,0	1,145	●
80 x	30 x	3,0	1,685	●
80 x	30 x	4,0	2,203	●
80 x	40 x	2,0	1,253	●
80 x	40 x	2,5	1,553	●
80 x	40 x	3,0	1,847	●
80 x	40 x	4,0	2,419	●
80 x	50 x	2,0	1,361	●
80 x	50 x	3,0	2,009	●
80 x	50 x	4,0	2,635	●
80 x	50 x	5,0	3,240	●
80 x	60 x	2,5	1,823 *	●
80 x	60 x	3,0	2,171 *	●
80 x	60 x	4,0	2,851	●
80 x	80 x	2,0	1,685	●
80 x	80 x	3,0	2,495	●
80 x	80 x	4,0	3,283	●
80 x	80 x	5,0	4,050 *	●
90 x	40 x	3,0	2,009 *	●
90 x	90 x	4,0	3,715 *	●
100 x	18 x	2,0	1,231	●
100 x	20 x	2,0	1,253	●

● auf Lager (1-2 bzw. 2-3 Arbeitstage) ● lieferbar (2-3 bzw. 3-4 Arbeitstage) * SA= Sonderabmessungen

weitere Abmessungen auf Anfrage




Vierkant- und Rechteckrohre

Legierung Al Mg Si 0,5 F 22 gepresst, warm ausgehärtet, in Herstellungslängen nach **EN 573 -3, 755 -1/ -2/ -9, DIN 1748 -4**

Höhe mm	Breite mm	Stärke mm	Gewicht kg/m	Al Mg Si 0,5 F 22 (EM AW-6060 T66)
100 x	25 x	2,0	1,307	●
100 x	30 x	2,0	1,361	●
100 x	30 x	3,0	2,009	●
100 x	40 x	2,0	1,469	●
100 x	40 x	2,5	1,832	●
100 x	40 x	3,0	2,171	●
100 x	40 x	4,0	2,851	●
100 x	50 x	2,0	1,577	●
100 x	50 x	3,0	2,333	●
100 x	50 x	4,0	3,067	●
100 x	50 x	5,0	3,780 *	●
100 x	60 x	2,0	1,685 *	●
100 x	60 x	3,0	2,495 *	●
100 x	60 x	4,0	3,283	●
100 x	60 x	5,0	4,050 *	●
100 x	80 x	2,5	2,363 *	●
100 x	80 x	3,0	2,819	●
100 x	100 x	2,0	2,117	●
100 x	100 x	3,0	3,143	●
100 x	100 x	4,0	4,147	●
100 x	100 x	5,0	5,130	●
100 x	50 x	2,5	2,093 *	●
110 x	60 x	4,0	3,499 *	●
110 x	20 x	2,0	1,469 *	●
120 x	30 x	2,0	1,577 *	●
120 x	30 x	3,0	2,333	●
120 x	40 x	2,0	1,685 *	●
120 x	40 x	2,5	2,093	●
120 x	40 x	3,0	2,495 *	●
120 x	40 x	4,0	3,283	●
120 x	50 x	3,0	2,657	●
120 x	50 x	4,0	3,499	●
120 x	60 x	3,0	2,819	●
120 x	60 x	4,0	3,715	●
120 x	80 x	3,0	3,143	●
120 x	120 x	2,5	3,173 *	●
120 x	120 x	4,0	5,011 *	●
120 x	120 x	5,0	6,210 *	●
130 x	30 x	3,0	2,495 *	●
130 x	50 x	4,0	3,715	●

● auf Lager (1-2 bzw. 2-3 Arbeitstage) ● lieferbar (2-3 bzw. 3-4 Arbeitstage) * SA= Sonderabmessungen

weitere Abmessungen auf Anfrage



Vierkant- und Rechteckrohre

Legierung Al Mg Si 0,5 F 22 gepresst, warm ausgehärtet, in Herstellungslängen nach **EN 573 -3, 755 -1/ -2/ -9, DIN 1748 -4**

Höhe mm	Breite mm	Stärke mm	Gewicht kg/m	Al Mg Si 0,5 F 22 (EM AW-6060 T66)
140 x	20 x	3,0	2,495 *	●
140 x	40 x	4,0	3,715	●
140 x	60 x	2,5	2,633 *	●
140 x	60 x	4,0	4,148 *	●
140 x	80 x	4,0	4,579	●
140 x	80 x	6,0	6,739 *	●
145 x	145 x	3,0	4,601 *	●
150 x	30 x	2,8	2,637 *	●
150 x	40 x	4,0	3,931	●
150 x	50 x	2,0	2,117 *	●
150 x	50 x	4,0	4,147	●
150 x	60 x	5,0	5,400 *	●
150 x	100 x	3,0	3,953	●
150 x	150 x	2,5	3,985 *	●
150 x	150 x	5,0	7,830 *	●
160 x	40 x	4,0	4,147 *	●
160 x	60 x	4,0	4,580 *	●
160 x	80 x	4,0	5,011 *	●
170 x	25 x	1,8	1,827 *	●
170 x	25 x	2,0	2,026 *	●
170 x	70 x	4,0	5,011 *	●
180 x	40 x	4,0	4,579	●
180 x	50 x	4,0	4,795	●
180 x	60 x	3,0	3,791 *	●
180 x	80 x	4,0	5,443 *	●
200 x	18 x	2,0	2,311 *	●
200 x	30 x	2,8	3,393 *	●
200 x	50 x	2,5	3,308	●
200 x	50 x	4,0	5,227	●
200 x	60 x	4,0	5,443	●
200 x	80 x	4,0	5,875 *	●
200 x	100 x	4,0	6,307 *	●
200 x	100 x	5,0	7,830 *	●
300 x	120 x	4,5	9,988 *	●